Software Test and Analysis in a Nutshell

Learning objectives

- View the "big picture" of software quality in the context of a software development project and organization:
- Introduce the range of software verification and validation activities
- Provide a rationale for selecting and combining them within a software development process.



c) 2007 Mauro Pezzè & Michal Young

Ch 1, slide 1



Engineering processes

- Sophisticated tools
 - amplify capabilities
 - but do not remove human error
- Engineering disciplines pair
 - construction activities with
 - activities that check intermediate and final products
- Software engineering is no exception: construction of high quality software requires
 - construction and
 - verification activities



2007 Mauro Pezzè & Michal Young



c) 2007 Mauro Pezzè & Michal Young

Ch 1, slide 2

Verification and design activities

- Verification and design activities take various forms
 - suited to highly repetitive construction of noncritical items for mass markets
 - highly customized or highly critical products.
- Appropriate verification activities depend on
 - engineering discipline
 - construction process
 - final product
 - quality requirements.



Peculiarities of software

Software has some characteristics that make V&V particularly difficult:

- Many different quality requirements
- Evolving (and deteriorating) structure
- Inherent non-linearity
- Uneven distribution of faults

Example

If an elevator can safely carry a load of 1000 kg, it can also safely carry any smaller load; If a procedure correctly sorts a set of 256 elements, it may fail on a set of 255 or 53 or 12 elements, as well as on 257 or 1023.



(c) 2007 Mauro Pezzè & Michal Young

Ch 1, slide 5

Variety of approaches

- There are no fixed recipes
- Test designers must
 - choose and schedule the right blend of techniques
 - to reach the required level of quality
 - within cost constraints
 - design a specific solution that suits
 - the problem
 - the requirements
 - the development environment



Impact of new technologies

- Advanced development technologies
 - can reduce the frequency of some classes of errors
 - but do not eliminate errors
- New development approaches can introduce new kinds of faults

examples

- deadlock or race conditions for distributed software
- new problems due to the use of polymorphism, dynamic binding and private state in object-oriented software.



(c) 2007 Mauro Pezzè & Michal Young

Ch 1, slide 6

Five Basic Questions

- 1. When do verification and validation start? When are they complete?
- 2. What particular techniques should be applied during development?
- 3. How can we assess the readiness of a product?
- 4. How can we control the quality of successive releases?
- 5. How can the development process itself be improved?



1: When do V&V start? When are they complete?

- Test is not a (late) phase of software development
 - Execution of tests is a small part of the verification and validation process
- V&V start as soon as we decide to build a software product, or even before
- V&V last far beyond the product delivery as long as the software is in use, to cope with evolution and adaptations to new conditions



(c) 2007 Mauro Pezzè & Michal Young

Ch 1, slide 9

Early start: from feasibility study

- The feasibility study of a new project must take into account the required qualities and their impact on the overall cost
- At this stage, quality related activities include
 - risk analysis
 - measures needed to assess and control quality at each stage of development.
 - assessment of the impact of new features and new quality requirements
 - contribution of quality control activities to development cost and schedule.



Ch 1, slide 10

Long lasting: beyond maintenance

- Maintenance activities include
 - analysis of changes and extensions
 - generation of new test suites for the added functionalities
 - re-executions of tests to check for non regression of software functionalities after changes and extensions
 - fault tracking and analysis

2: What particular techniques should be applied during development?

No single A&T technique can serve all purposes

The primary reasons for combining techniques are:

- Effectiveness for different classes of faults example: analysis instead of testing for race conditions
- Applicability at different points in a project example: inspection for early requirements validation
- Differences in purpose example: statistical testing to measure reliability
- Tradeoffs in cost and assurance example: expensive technique for key properties





Staging A&T techniques

Requirements Elicitation	Requirements Specification	Architectural Design	Detailed Design	Unit Coding	Integration & Delivery	Maintenanc
Identify qualit	es					
Plan acceptar	ce test					
а П	Dian custom toot					
je L	i tun system test					
Plan		Plan unit & int	egration test			
			Monitor the	Att I process		
8 (Validate specific	ations				
of	Ana	lyze architectura	ıl design			
atio	In	spect architectur	al design			
Ŭ.		Inst	pect detailed des	ign		
A6				Code inspe	ction	
22	Conorate	tom toot		L		
161	Generate sys	cent cesc				
8	Generate integration test					
Lati,		G	enerate unit test	_		
jeg.				G	enerate regressio	on test
0					Update	regression te
5			Design scaffolding	8		
idat			Design oracles			
r va				Execute unit te	st	
s pu				Analyze cov	erage	
D UG			4	Generate str	uctural text	
crti				Generate sti	accuractest	
500				Exe	ute integration	Lest
8					Execute system	test
tet					Execute accep	tance test
					Execute r	egression test
ement					Collect data on fa	ults
e ou				Lanature	foulte and imme	
·,⊑				Lanatyz	- radius and impr	ove the proce
() 0007.14		1 1 1 1				

3: How can we assess the readiness of a product?

- A&T during development aim at revealing faults
- We cannot reveal are remove all faults
- A&T cannot last indefinitely: we want to know if products meet the quality requirements
- We must specify the required level of dependability
- and determine when that level has been attained.



(c) 2007 Mauro Pezzè & Michal Young

Different measures of dependability

- Availability measures the quality of service in terms of running versus down time
- Mean time between failures (MTBF) measures the quality of the service in terms of time between failures
- Reliability indicates the fraction of all attempted operations that complete successfully

Example of different dependability measures

Web application:

- 50 interactions terminating with a credit card charge.
- The software always operates flawlessly up to the point that a credit card is to be charged, but on half the attempts it charges the wrong amount.

What is the reliability of the system?

2007 Mauro Pezzè & Michal Young

- If we count the fraction of individual interactions that are correctly carried out, only one operation in 100 fail: The system is 99% reliable.
- If we count entire sessions, only 50% reliable, since half the sessions result in an improper credit card charge



State State

Assessing dependability

- Randomly generated tests following an operational profile
- Alpha test: tests performed by users in a controlled environment, observed by the development organization
- Beta test: tests performed by real users in their own environment, performing actual tasks without interference or close monitoring

SOFTWARE TESTING AND ANALYSIS	
East No	_

(c) 2007 Mauro Pezzè & Michal Young

Ch 1, slide 17

4: How can we control the quality of successive releases?

- Software test and analysis does not stop at the first release.
- Software products operate for many years, and undergo many changes:
 - They adapt to environment changes
 - They evolve to serve new and changing user requirements.
- Quality tasks after delivery
 - test and analysis of new and modified code
 - re-execution of system tests
 - extensive record-keeping



Ch 1, slide 18

5: How can the development process itself be improved?

- The same defects are encountered in project after project
- A third goal of the improving the quality process is to improve the process by
 - identifying and removing weaknesses in the development process
 - identifying and removing weaknesses in test and analysis that allow them to remain undetected

A four step process to improve fault analysis and process

- 1. Define the data to be collected and implementing procedures for collecting them
- 2. Analyze collected data to identify important fault classes
- 3. Analyze selected fault classes to identify weaknesses in development and quality measures
- 4. Adjust the quality and development process





An example of process improvement

- 1. Faults that affect security were given highest priority
- 2. During A&T we identified several buffer overflow problems that may affect security
- 3. Faults were due to bad programming practice and were revealed late due to lack of analysis
- 4. Action plan: Modify programming discipline and environment and add specific entries to inspection checklists



(c) 2007 Mauro Pezzè & Michal Young

Ch 1, slide 21

Summary

- The quality process has three different goals:
 - Improving a software product
 - assessing the quality of the software product
 - improving the quality process
- We need to combine several A&T techniques through the software process
- A&T depend on organization and application domain.
- Cost-effectiveness depends on the extent to which techniques can be re-applied as the product evolves.
- Planning and monitoring are essential to evaluate and refine the quality process.



(c) 2007 Mauro Pezzè & Michal Young

Ch 1, slide 22